

Timeclock Guide – ATS 700 Wi-Fi Adapter Installation Guide

Overview:

- Installing the ATS Wi-Fi Adapter
- Configure the ATS 700 timeclock to connect to your Wi-Fi network

Installing the ATS Wi-Fi Adapter

- 1) Power the timeclock off
- 2) **Unlock** the ATS 700 timeclock
- 3) Insert the RAlink Wi-Fi adapter with antenna into an available USB port.



4) Power the timeclock back **on**.

Configure the ATS 700 Timeclock for Wi-Fi

- 1) On the timeclock, tap the Wrench Icon 🖊
- 2) Enter the Setup Password (Common passwords: 1234 or clock's serial number), Tap Enter



3) Tap Setup





Timeclock Guide – ATS 700 Wi-Fi Adapter Installation Guide

4) Enter Setup Password, tap Enter Setup



5) Check the box next to Wi-Fi, tap Configure

Interfaces	Options	Administration	Info	
		Terminal Interfaces		
V Ethernet:	Configure		WiFi: Config	ure
Cellular:	Configure		Serial: Config	ure
	Host Int	erface: Configure		
S	ave	Cancel	Reb	oot

6) Expand the drop-down box next to **SSID**, tap your Network Name



Note: If your network does not appear > Enter the network name in the Hidden SSID field. This field is case sensitive.





Timeclock Guide – ATS 700 Wi-Fi Adapter Installation Guide

7) In the Key field, enter your Wi-Fi password

Interfaces	Options	Administration	Info	
		WiFi Configuratio	on	
рнср 🗸	IP;		Mask:	
	Gateway:		DNS: 8.8.8.8	
SSID:	Konosuba	∽ Key: ∙	••••••••••••••••••••••••••••••••••••••	• • •
lidden SSID:				
0	Save	Cancel	Reboo	

8) Tap **Save** and wait 15 seconds

Interfaces	Option	15 /	Administration	Info	
		Wif	i Configuration		
рнср 🗸	IP:			Mask	
	Gateway:			DNS: 8.8.8	
SSID:	Konosuba	~	Key: 😶	•••••• <mark>••••••</mark> •••••	
Hidden SSID:					
\bigcirc	Save		Cancel	Reboot	?

9) A status will appear upon saving.

Interfaces	Options	Administration	Info
		WiFi Configuration	
DHCP 🔽	IP:		Mask
	Gateway:		DNS: 8.8.8.8
SSID:	Konosuba	✓ Key: ····	•••••• <mark>•••••</mark> ••••
Hidden SSID:		Status: con	nected (Konosuba – 100%)
0	Save	Cancel	Reboot

Connected: We highly recommend at least 70% connectivity. If your percentage is lower, we recommend moving the clock closer to the router.

Disconnected: Verify your Wi-Fi network information. If the network information is correct, reach out to our support team for further assistance. In some cases, we may ask for your IT or internet service provider to be involved to verify network settings.